

CLAIMS

- sub A1 >
1. An electron beam collector comprising:
 - an electrically conductive dissipation cavity;
 - a front wall located at one side of said dissipation cavity having an aperture to allow the passage of the electron beam into the cavity;
 - a rear wall in said dissipation cavity, opposite the front wall, positioned and shaped such that electrons which strike it, and secondary electrons, are captured in said dissipation cavity; and
 - a voltage source electrically connected to said collector.
 2. A depressed voltage collector for use with a device emitting an electron beam containing electrons traversing into the collector where energy is recovered from the electron beam, said collector comprising:
 - means for depressing the voltage of said collector; and
 - means for trapping said electrons after they exit said electron beam device.
 3. A depressed collector for use with a device emitting an electron beam containing electrons traversing into the collector where energy is recovered from the electron beam, said collector comprising:
 - means for decelerating said electrons after they exit said electron beam device; and
 - means for trapping said electrons after they exit said electron beam device.
 4. A depressed voltage collector for use with a device emitting a sheet electron beam containing electrons traversing into the collector where energy is recovered from the electron beam, said collector comprising:
 - means for depressing said voltage of said collector; and
 - means for trapping said electrons after they exit said electron beam device.

10038016-040502
205040-91082001

5. A depressed voltage collector for use with a device emitting a large aspect ratio annular electron beam containing electrons traversing into the collector where energy is recovered from the electron beam, said collector comprising:

means for depressing said voltage of said collector; and

means for trapping said electrons after they exit said electron beam device.

sub A2 > 6. A depressed voltage collector for use with a device emitting an electron beam containing electrons traversing into the collector where energy is recovered from the electron beam, said collector comprising:

an electrically conductive dissipation cavity;

10038016-040502 205040-9T0800T a front wall located at one side of said dissipation cavity having an aperture to allow the passage of said electron beam into said cavity;

a rear wall in said dissipation cavity, opposite said front wall, positioned and shaped such that said electrons which strike it, and secondary electrons, are captured in said dissipation cavity; and

a voltage source electrically connected to the collector and to the device.

7. The collector of claim 6 wherein said rear wall is planar.

8. The collector of claim 6 wherein said rear wall is shaped such that said reflected electrons and said secondary electrons are captured in said dissipation cavity.

sub A3 > 9. A depressed voltage collector for use with a device emitting a rectangular sheet electron beam of electrons traversing into the collector where energy is recovered from the electron beam, said collector comprising:

an electrically conductive dissipation cavity;

a front wall located at one side of said dissipation cavity having an aperture to allow the passage of said rectangular sheet electron beam into said cavity;

Sub
A3
cont'd

a rear wall in said dissipation cavity, opposite said front wall, positioned and shaped such that said electrons which strike it, and secondary electrons, are captured in said dissipation cavity; and

a voltage source electrically connected to said collector and to said device.

10. A depressed voltage collector for use with a device emitting a large aspect ratio annular electron beam of electrons traversing into the collector where energy is recovered from the electron beam, said collector comprising:

an electrically conductive dissipation cavity;

a front wall located at one side of said dissipation cavity having an annular aperture to allow the passage of said annular electron beam into said cavity;

a rear wall in said dissipation cavity, opposite said front wall, positioned and shaped such that said electrons which strike it, and secondary electrons, are captured in said dissipation cavity; and

a voltage source electrically connected to said collector and to said device.

11. A depressed voltage collector for connection to a submillimeter electromagnetic wave device containing a cathode and a body generating a rectangular sheet electron beam of electrons traversing into the collector where energy is recovered from the electron beam, said collector comprising:

an electrically conductive dissipation cavity;

a front wall located on one side of said dissipation cavity having a rectangular aperture to allow passage of said rectangular sheet electron beam into said interior cavity;

a conductive reflector electrically and mechanically attached to said interior cavity in said enclosure, opposite said rectangular aperture, positioned at an angle to said incident rectangular sheet electron beam to reflect the electrons into the interior cavity; and

10036015-040502

means for electrically energizing said collector such that the total voltage difference between said collector and said cathode is significantly less than the voltage difference between said cathode and said device body.

12. A single stage depressed voltage collector for use with a device emitting an electron beam containing electrons traversing into the collector where energy is recovered from the electron beam, said collector comprising:

means for depressing the voltage of said collector; and

means for trapping said electrons after they exit said electron beam device.

13. A single stage depressed voltage collector for use with a device emitting an electron beam containing electrons traversing into the collector where energy is recovered from the electron beam, said collector comprising:

an electrically conductive dissipation cavity;

a front wall located at one side of said dissipation cavity having an aperture to allow the passage of said electron beam into said cavity;

a rear wall in said dissipation cavity, opposite said front wall, positioned and shaped such that said electrons which strike it, and secondary electrons, are captured in said dissipation cavity; and

a voltage source electrically connected to the collector and to the device.

14. The collector of claim 13 wherein said rear wall is planar.

15. The collector of claim 13 wherein said rear wall is shaped such that said reflected electrons and said secondary electrons are captured in said dissipation cavity.

16. A single stage depressed voltage collector for connection to a submillimeter electromagnetic wave device containing a cathode and a body generating a rectangular sheet electron beam of electrons traversing into the collector where energy is recovered from the electron beam, said collector comprising:

Sub
A4

10038016-040502

an electrically conductive dissipation cavity;

a front wall located on one side of said dissipation cavity having a rectangular aperture to allow passage of said rectangular sheet electron beam into said interior cavity;

a conductive reflector electrically and mechanically attached to said interior cavity in said enclosure, opposite said rectangular aperture, positioned at an angle to said incident rectangular sheet electron beam to reflect the electrons into the interior cavity; and

means for electrically energizing said collector such that the total voltage difference between said collector and said cathode is significantly less than the voltage difference between said cathode and said device body.

17. A method for recovering energy from an electron beam containing electrons emerging from an electromagnetic wave device into a collector, comprising:

depressing the voltage of the collector; and

trapping said electrons in the collector.

18. The method of claim 17 wherein said electron beam is a sheet electron beam.

19. The method of claim 17 wherein said electron beam is a large aspect ratio annular electron beam.

20250409-040502